

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Laumela Chalk Paint VINTAGE

Other names: Chalk Paint VINTAGE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Chalk paint intended for painting absorbent and smooth surfaces (wood, MDF board, metal, plastic, walls, floors, clay pots, wicker). Recommended for styling and painting furniture.

Detailed information on the use, properties and method of application of the product is given in the technical data sheet.

Uses advised against: Other than indicated above.

1.3 Details of the supplier of the safety data sheet

Zakłady Chemiczne „ANSER” Sp. z o.o.

ul. Dźwigowa 3/2, 02-437 Warszawa, Poland

Tel.: +48 46 856 73 40 fax: +48 46 856 73 50

email: a.zagajewska@anser.pl

1.4 Emergency telephone number

Emergency telephone number in Poland (available 8:00 a.m. – 4:00 p.m.): +48 46 856 73 40

112 (emergency number), 998 (fire brigade), 999 (medical emergency)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008:

Hazards arising from physicochemical properties:

The mixture is not classified as presenting a hazard with regard to physicochemical properties.

Hazards to health

The mixture is not classified as presenting a hazard to health. See additional labelling.

Hazards to the environment:

The mixture does not present a hazard to the environment. No effects on the environment are known or expected under normal conditions of use.

2.2 Label elements

General:

P102 Keep out of reach of children.

Response:

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Supplemental hazard statements:

EUH208 Contains [1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiazol-3-one]. May produce an allergic reaction.

EUH210 Safety data sheet available on request. [Mixtures not intended for the general public].

2.3 Other hazards

The substances contained in the product do not meet the PBT or vPvB criteria in accordance with Annex XIII to the REACH Regulation.

PBT substances (persistent, bioaccumulative and toxic substances).

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

vPvB substances (substances that are very persistent and very bioaccumulative).

The product does not contain substances included in the list drawn up in accordance with Article 59(1) as having endocrine-disrupting properties, or substances identified as having endocrine-disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not applicable.

3.2 Mixture

Identification numbers	Chemical name	wt. %	Pictogram, signal word codes	Hazard class and category codes	H-statement codes
CAS: 2634-33-5 EC (EINECS): 220-120-9 Index No.: 613-088-00-6 Own registration number: —	1,2-benzisothiazol-3(2H)-one	<0.0015	GHS09 GHS05 GHS07 Dgr	Acute Tox. 4 Skin Irrit. 2 Skin Sens. 1 Eye Dam. 1 Aquatic Acute 1 H400 (M=10) Specific concentration limits: Skin Sens. 1 H317: C ≥ 0.05%	H302 H315 H317 H318 H400
CAS: 2682-20-4 EC (EINECS): 220-239-6 Index No.: 613-326-00-9 Own registration number: 01-2120764690-50-xxxx	2-methyl-2H-isothiazol-3-one	<0.0015	GHS09 GHS05 GHS06 Dgr	Acute Tox. 3 Acute Tox. 3 Acute Tox. 2 Skin Corr. 1B Skin Sens. 1A Eye Dam. 1 Aquatic Acute 1 M=10 Aquatic Chronic 1 M=1 Specific concentration limit: Skin Sens. 1A: C ≥ 0.0015%	H301 H311 H330 H314 H317 H400 H410

Substances with an established maximum permissible workplace exposure concentration

CAS: 13463-67-7 EC (EINECS): 236-675-5 Index No.: 022-006-00-2 Own registration number: 01-2119489379-17-xxxx Titanium dioxide in powder form with a content of <1% of particles of aerodynamic diameter ≤ 10 µm [1,3] 2<x<8 ____ Substance not classified as presenting a hazard ____

[1] substance with a nationally established maximum permissible workplace exposure concentration value. See Section 8.

[3] Note 10: Classification as a substance carcinogenic via the respiratory route applies only to mixtures in powder form containing 1% or more of titanium dioxide in the form of particles of aerodynamic diameter ≤ 10 µm, or incorporated into such particles.

Full text of H statements is given in point 16 of the Safety Data Sheet.

SAFETY DATA SHEET

Revision date: 11.09.2026

VERSION: 1/EN

Laumela Chalk Paint VINTAGE**Chalk Paint VINTAGE**

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

General remarks: If any worrying symptoms occur, call a doctor and show the label or Safety Data Sheet. Never give anything by mouth to an unconscious or drowsy person.

Inhalation: In case of feeling unwell, provide access to fresh air. Call a doctor if necessary.

Skin contact: Remove contaminated clothing. Wash exposed areas of skin thoroughly with soap and water. If worrying symptoms occur, contact a doctor. Wash clothing before reuse. Do not use solvents or thinners.

Eye contact: Rinse with plenty of cool water, preferably running water, for at least 15 minutes. Remove contact lenses. Avoid a strong stream of water due to the risk of mechanical damage to the cornea. If irritation persists, consult an ophthalmologist.

Digestive tract: If a large amount has been swallowed, do not induce vomiting without consulting a doctor. Rinse the mouth with plenty of water. Contact a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Follow the safety and use precautions given on the label. Immediately remove the product from the skin, eyes and mucous membranes, which will help prevent any delayed effects of exposure.

Skin contact: Prolonged skin contact may cause dryness, burning, redness. Sensitive individuals may experience an allergic reaction.

Eye contact: If the product gets into the eyes, tearing, discomfort and temporary irritation may occur.

Ingestion: Swallowing the product causes abdominal pain and vomiting.

Inhalation: Vapours may cause coughing, irritate the respiratory tract.

4.3 Indication of any immediate medical attention and special treatment needed

Show the safety data sheet or label/packaging to the medical personnel providing assistance. Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

The product is non-flammable under normal conditions of handling, storage and use. In the event of ignition due to improper handling, storage or use, apply:

Suitable extinguishing media:

Foam, carbon dioxide, extinguishing powders, water — spray jets.

Unsuitable extinguishing media:

Do not use a solid water jet.

5.2 Special hazards arising from the substance or mixture

Toxic combustion products, including carbon oxides and other unidentified thermal decomposition products, may be formed during combustion. Avoid inhaling combustion products, which may pose a health hazard.

5.3 Advice for firefighters

Follow the procedures applicable to fighting chemical fires. General protective measures typical for fires. Do not remain in the fire-endangered zone without appropriate chemical-resistant clothing and self-contained breathing apparatus. Collect used extinguishing agents. Remain in the hazard zone only with independent breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

For non-emergency personnel:

Restrict access of unauthorised persons to the accident area until the appropriate clean-up operations have been completed. In case of large spills, isolate the endangered area. Use personal protective equipment. Avoid contamination of eyes and skin. Ensure adequate ventilation.

For emergency responders:

Ensure that the clean-up of the incident and its effects is carried out only by trained personnel. Use personal protective equipment.

6.2 Environmental precautions

Do not allow the product to enter drains, watercourses or soil. In case of release of large quantities of the product, notify the relevant authorities.

6.3 Methods and material for containment and cleaning up

Protect drains. Absorb the product using a chemically inert binding material (sand, diatomaceous earth), transfer to tightly sealed containers and send for disposal. Rinse the contaminated surface with plenty of water.

Dispose of the contaminated material as waste, following the procedure given in Section 13.

6.4 Reference to other sections

Personal protective equipment — see Section 8. Dispose of in accordance with the recommendations given in Section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Work in accordance with health and safety rules. Avoid contact with eyes and skin. Avoid inhaling product vapours. Wash hands before breaks and after finishing work. Keep unused containers tightly closed. Ensure proper ventilation of the room where the product is stored and used. Remove sources of ignition, do not smoke. Use personal protective equipment. Use as intended.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Store the product in a cool, dry and well-ventilated place. Optimal storage temperature +5 to +25°C. Shelf life from the date of production is 2 years. Keep the product away from heat and heating systems. Protect from frost. After opening, reseal the container and store it upright to avoid leakage.

7.3 Specific end use(s)

See Section 1.2 of the SDS. No information on other uses.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

PL: Titanium dioxide [13463-67-7] — inhalable fraction

NDS: 10 mg/m³

Legal basis:

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on maximum permissible concentrations and intensities of factors harmful to health in the working environment (Journal of Laws 2018.1286 of 3 July 2018, as amended [Journal of Laws 2020.61 of 17.01.2020; Journal of Laws 2023 item 1658]).

Regulation of the Minister of Development, Labour and Technology of 18 February 2021 amending the regulation on maximum permissible concentrations and intensities of factors harmful to health in the working environment [Journal of Laws 2021 item 325].

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of factors harmful to health in the working environment (Journal of Laws No. 33, item 166, 2011, as amended by Journal of Laws 2022.2662).

DNEL and PNEC values: No data.

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Recommended monitoring procedures:

Procedures for monitoring the concentrations of hazardous components in the air and procedures for controlling air purity in the workplace should be applied — where available and justified for a given position — in accordance with the relevant Polish or European Standards, taking into account the conditions prevailing at the place of exposure and appropriate measurement methodology adapted to the working conditions. The mode, type and frequency of tests and measurements should meet the requirements set out in the Regulation of the Minister of Health of 2 February 2011 (Journal of Laws 2011 No. 33, item 166, as amended — consolidated text Journal of Laws 2023 item 419).

8.2 Exposure controls

8.2.1 Appropriate technical control measures

If the exposure level exceeds the NDS level, appropriate respiratory protective equipment is required.

8.2.2 Individual protection measures, such as personal protective equipment

When the concentration of hazardous substances at the workplace is determined and known, the choice of personal protective equipment should take into account the concentration present, the duration of exposure, the activities performed by the worker, and the manufacturer's recommendations for the protective equipment. In an emergency situation, or when the concentration at the workplace is unknown, use isolating personal protective equipment (a gas-tight suit combined with isolating respiratory protection).

Respiratory tract: Not necessary under normal conditions with adequate ventilation. Use in well-ventilated rooms. In confined spaces / insufficient oxygen content in the air, high uncontrolled emissions, and in all circumstances where a filtering mask does not provide sufficient protection, use isolating respiratory protective equipment.

Hands and skin: Not necessary. Use suitable protective gloves in case of direct or prolonged contact with the product. Select glove material individually for the workplace. Wear protective clothing. Glove material must be impermeable and resistant to the product. The resistance of glove materials must be checked before use. Obtain information on breakthrough time from the glove manufacturer and observe it. It is recommended to change gloves regularly and replace them immediately if there are any signs of wear, damage (tears, punctures) or changes in appearance (colour, elasticity, shape).

Eyes: Protect from contact with the eyes.

Occupational hygiene: General industrial occupational hygiene rules apply. Remove contaminated clothing after finishing work. Wash hands and face before breaks. Wash the whole body thoroughly after work. Do not eat, drink or smoke while working.

8.2.3 Environmental exposure controls

Any emissions from ventilation systems and process equipment should be checked for compliance with environmental protection legal requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Property	Value
Physical state	Liquid
Colour	No data
Odour	Odourless
Melting point/freezing point	No data
Boiling point and boiling range	No data
Flammability	Non-flammable product
Lower and upper explosive limit	No data
Flash point	No data
Auto-ignition temperature [gases, liquids]	No data

SAFETY DATA SHEET

Revision date: 11.09.2026

VERSION: 1/EN

Laumela Chalk Paint VINTAGE
Chalk Paint VINTAGE

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Property	Value
Decomposition temperature	No data
pH	No data
Kinematic viscosity [mm ² /s]	No data
Solubility	Soluble in water
Partition coefficient: n-octanol/water	No data
Vapour pressure	No data
Relative density	approx. 1.7 g/cm ³
Relative vapour density	No data
Particle characteristics [solid]	Not applicable [liquid]

9.2 Other information**9.2.1 Information with regard to physical hazard classes**

No results of additional testing.

9.2.2 Other safety characteristics

No results of additional testing.

SECTION 10: STABILITY AND REACTIVITY**10.1 Reactivity**

Under conditions of storage and handling as intended — no reactivity.

10.2 Chemical stability

Under normal conditions of use and storage, the product is stable.

10.3 Possibility of hazardous reactions

No hazardous reactions are known.

10.4 Conditions to avoid

Avoid high temperatures, direct sunlight; protect from frost.

10.5 Incompatible materials

Strong oxidisers.

10.6 Hazardous decomposition products

Depending on the decomposition conditions, complex mixtures of chemical substances may be released, including carbon dioxide (CO₂), carbon monoxide, and other organic compounds. For more information see Section 5.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute toxicity

ATEmix oral (mg/kg): >2000. Based on the available data, the classification criteria are not met.

ATEmix dermal (mg/kg): >2000. Based on the available data, the classification criteria are not met.

ATEmix inhalation (mg/l/4h): >20. Based on the available data, the classification criteria are not met.

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

The acute toxicity of the mixture (ATEmix) was calculated on the basis of the relevant conversion factor contained in Table 3.1.2 of Annex I to the CLP Regulation, as amended.

Skin corrosion/irritation:

Based on the available data, the classification criteria are not met.

Serious eye damage/eye irritation:

Based on the available data, the classification criteria are not met.

Respiratory or skin sensitisation:

EUH208 Contains [1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiazol-3-one]. May produce an allergic reaction.

Germ cell mutagenicity:

Based on the available data, the classification criteria are not met.

Carcinogenicity:

Based on the available data, the classification criteria are not met.

Reproductive toxicity:

Based on the available data, the classification criteria are not met.

Specific target organ toxicity — single exposure:

Based on the available data, the classification criteria are not met.

Specific target organ toxicity — repeated exposure:

Based on the available data, the classification criteria are not met.

Aspiration hazard:

Based on the available data, the classification criteria are not met.

Information on likely routes of exposure

Skin contact: Prolonged skin contact may cause dryness, burning, redness. Sensitive individuals may experience an allergic reaction.

Eye contact: If the product gets into the eyes, tearing, discomfort and temporary irritation may occur.

Ingestion: Swallowing the product causes abdominal pain and vomiting.

Inhalation: Vapours may cause coughing, irritate the respiratory tract.

11.2 Information on other hazards

Endocrine-disrupting properties:

The product has no effect on the endocrine system in accordance with the assessment criteria set out in Regulations (EC) No 1907/2006, (EU) 2017/2100, (EU) 2018/605.

Other information:

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity of the mixture

The mixture does not present a hazard to the environment. No effects on the environment are known or expected under normal conditions of use.

To minimise long-term global pollution, consider:

Reducing the consumption of single-use products and packaging.

Participating in recycling activities.

Not allowing the product to enter water, sewage or soil.

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

12.2 Persistence and degradability

No data for the mixture.

12.3 Bioaccumulative potential

No data for the mixture.

12.4 Mobility in soil

The product is soluble in water. The mobility of substances depends on their hydrophilic and hydrophobic properties and on the abiotic and biotic conditions of the soil, including its structure, climatic conditions, season (in Poland, in a temperate transitional climate), and soil organisms, mainly bacteria, fungi, algae and invertebrates.

12.5 Results of PBT and vPvB assessment

Does not meet the PBT and vPvB criteria.

12.6 Endocrine-disrupting properties

The product does not contain components included in the list drawn up in accordance with Article 59(1) as having endocrine-disrupting properties, nor components with endocrine-disrupting properties in accordance with the criteria set out in Regulation (EU) 2017/2100 or Regulation (EU) 2018/605, at a concentration equal to or greater than 0.1%.

12.7 Other adverse effects

The mixture is not classified as presenting a hazard to the ozone layer. The possibility of other adverse effects of the individual components of the mixture on the environment should be considered (e.g. potential for endocrine disruption, contribution to global warming).

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product disposal:

If possible, recover the waste. In accordance with the law applicable in Poland, waste collection, disposal, recovery or recycling may only be carried out by, and waste may only be transferred to, establishments holding the appropriate authorisations. In case of doubt, agree the method of waste management with the local Environmental Protection Inspectorate unit.

The waste code should be assigned at the place of its generation.

Proposed waste code

Waste code: 08 01 12 — Waste paint and varnish other than those mentioned in 08 01 11.

Packaging disposal: Recovery (recycling) or disposal of packaging waste should be carried out in accordance with the applicable regulations. Reusable packaging, after cleaning, should be reused. Waste disposal should be carried out in professional, authorised incineration plants or waste treatment and disposal facilities.

Waste code: 15 01 02 — Plastic packaging.

Legal basis:

EU legal acts: Directives of the European Parliament and of the Council: 2008/98/EC, as amended, 94/62/EC, as amended.

National legal acts: on waste, Journal of Laws 2013 item 21, as amended; on packaging and packaging waste management, Journal of Laws 2013, item 888, as amended.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

The product is not subject to the regulations on the transport of dangerous goods contained in ADR (road transport), RID (rail transport), IMDG (sea transport), ICAO/IATA (air transport).

14.2 UN proper shipping name

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Not applicable.

14.3 Transport hazard class(es)

Not applicable.

14.4 Packing group

Not applicable.

14.5 Environmental hazards

The product does not present a hazard to the environment in accordance with the criteria contained in the UN Model Regulations.

14.6 Special precautions for user

No special precautions.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations

1. 1907/2006/EC Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
2. 1272/2008/EC Regulation of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
3. 2020/878/EU Commission Regulation of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals.
4. REGULATION (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents.
5. 94/62/EC Directive of the European Parliament and of the Council of 20 December 1994 on packaging and packaging waste, as amended.
6. Act of 25 February 2011 on chemical substances and their mixtures (Journal of Laws 2011 No. 63 item 322, consolidated text Journal of Laws 2022 item 1816).
7. Act of 13 June 2013 on packaging and packaging waste management (Journal of Laws 2013 item 888, consolidated text Journal of Laws 2023 item 1658).
8. Act on the carriage of dangerous goods of 19 August 2011 (Journal of Laws No. 227, item 1367), consolidated text Journal of Laws 2022 item 2147.
9. Government Declaration of 13 March 2023 on the entry into force of amendments to Annexes A and B to the European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), done at Geneva on 30 September 1957 (Journal of Laws 2023 item 891).

15.2 Chemical safety assessment

The supplier has not carried out a chemical safety assessment. A chemical safety report is not required for the mixture.

SECTION 16: OTHER INFORMATION

Other sources of data:

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

IUCLID Data Bank (European Commission – European Chemicals Bureau).

ESIS – European Chemical Substances Information System (European Chemicals Bureau).

Safety data sheet prepared by: Małgorzata Krenke [Based on the supplier's safety data sheet]

Feed Reach Consulting; E-mail: biuro@frc.com.pl

The above information has been prepared based on currently available data characterising the product and the manufacturer's experience and knowledge in this field. The data contained in this Safety Data Sheet should be treated solely as an aid for safe handling in transport, distribution, use and storage. This Safety Data Sheet is not a certificate of product quality. The information contained in this Safety Data Sheet relates only to the named product and may not be valid or sufficient for this product used in combination with other materials or for other uses. The user of the product is obliged to comply with all applicable standards and regulations and bears responsibility arising from improper use of the information contained in this Safety Data Sheet or improper use of the product.

Classification and procedures used to classify the mixture in accordance with Regulation (EC) 1272/2008 [CLP]

Hazards arising from physicochemical properties:

The mixture is not classified as presenting a hazard with regard to physicochemical properties.

Hazards to health

The mixture is not classified as presenting a hazard to health. EUH208 Contains [1,2-benzisothiazol-3(2H)-one; 2-methyl-2H-isothiazol-3-one]. May produce an allergic reaction.

Hazards to the environment:

The mixture does not present a hazard to the environment. No effects on the environment are known or expected under normal conditions of use.

H-statements (indicating the type of hazard) used in Sections 2 and 3 of the Safety Data Sheet:

H317 May cause an allergic skin reaction.

Skin Sens. 1 Skin sensitisation, Hazard Category 1

H301 Toxic if swallowed

Acute Tox. 3 Acute toxicity (oral), Hazard Category 3

H314 Causes severe skin burns and eye damage

Skin Corr. 1B Skin corrosion/irritation, Hazard Category 1, subcategory 1B

H400 Very toxic to aquatic life.

Aquatic Acute 1 Hazardous to the aquatic environment, Hazard Category 1

H410 Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 1 Hazardous to the aquatic environment, Hazard Category 1

H318 Causes serious eye damage

Eye Dam. 1 Serious eye damage/eye irritation, Hazard Category 1

H330 Fatal if inhaled

Acute Tox. 2 Acute toxicity (inhalation), Hazard Category 2

H315 Causes skin irritation

Skin Irrit. 2 Skin irritation, Hazard Category 2

H311 Toxic in contact with skin

Acute Tox. 3 Acute toxicity (dermal), Hazard Category 3

H302 Harmful if swallowed

Acute Tox. 4 Acute toxicity (oral), Hazard Category 4

Explanation of abbreviations and acronyms

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Abbreviation	Meaning
CEN	European Committee for Standardization
C&L	Classification and Labelling
CLP	Regulation on Classification, Labelling and Packaging; Regulation (EC) No 1272/2008
CAS	Chemical Abstracts Service number
COM	European Commission
CMR	Carcinogenic, mutagenic or toxic to reproduction
CSA	Chemical Safety Assessment
CSR	Chemical Safety Report
DMEL	Derived Minimal Effect Level
DNEL	Derived No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EEC
DSD	Dangerous Substances Directive 67/548/EEC
EC	European Commission
EC50	Median effective concentration
ECB	European Chemicals Bureau
ECHA	European Chemicals Agency
EC	EINECS and ELINCS number (see also EINECS and ELINCS)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Standard
EU	European Union
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IC50	Concentration causing 50 percent inhibition of a given parameter
IUCLID	International Uniform Chemical Information Database
IUPAC	International Union of Pure and Applied Chemistry
LC50	Median lethal concentration
LD50	Median lethal dose
MSDS	Material Safety Data Sheet
PBT	Persistent, bioaccumulative and toxic substance
PEC	Predicted environmental concentration
PNEC(s)	Predicted no-effect concentration(s)
PPE	Personal protective equipment
REACH	Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
SDS	Safety Data Sheet

SAFETY DATA SHEET 	Revision date: 11.09.2026 VERSION: 1/EN
Laumela Chalk Paint VINTAGE Chalk Paint VINTAGE	

prepared in accordance with Commission Regulation (EU) No 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Abbreviation	Meaning
SIEF	Substance Information Exchange Forum
STOT	Specific target organ toxicity
(STOT) RE	Repeated exposure
(STOT) SE	Single exposure
SVHC	Substance of Very High Concern
vPvB	Very persistent and very bioaccumulative [substance]
UN number	Material identification number under the ADR agreement.
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
MARPOL	International Convention for the Prevention of Pollution from Ships (MARPOL)
EmS	Emergency Schedules for ships carrying dangerous goods
NDS	Occupational exposure limit — time-weighted average (TLV-TWA) (OEL-TWA) (PEL-TWA)
NDSch	Short-term exposure limit (TLV-STEL)
NDSP	Ceiling occupational exposure limit (TLV-C)

Training

Before starting work with the product, the user should familiarise themselves with occupational health and safety rules regarding the handling of chemicals, and in particular undergo appropriate workstation training.

VERSION: 1